


DRILLING COMPANY: **WEST HAZMAT DRILLING**      RIG: **C.M.E. 75**      DATE: **1/31/01**  
 BORING DIAMETER: **8 INCHES**      DRIVE WEIGHT (S): **140 LB**      DROP: **30 INCHES**      ELEVATION: **~40 FT MSL**

# BORING NO. MW-6

DEPTH (FEET)	BAG SAMPLE	DRIVE SAMPLE	BLOWS/FOOT	CHEM ANALYSIS		LITHOGRAPHIC CLASS	SOIL CLASS (U.S.C.S)	LITHOLOGIC DESCRIPTIONS	WELL CONSTRUCTION
				TPH GAS (ppm)	TPH DIESEL (ppm)				
0								3" ASPHALT; BASE FILL - MEDIUM SAND AND 2" COBBLES	TRAFFIC-RATED STEEL WELL COVER AND LOCKING PLUG AT SURFACE.
								BAY POINT FM - MODERATE REDDISH BROWN CL. SLIGHTLY SANDY LEAN CLAY, STIFF, DAMP	REDI-CRETE AND RAPID-SET MIX SURFACE SEAL 0-2 FEET.
5	X		8	ND	ND				BENTONITE GROUT 2-14 FEET. BENTONITE CHIPS PLACED THROUGH CENTER OF AUGER 14-18 FEET.
10	X		24	ND	ND			CL LIGHT REDDISH BROWN SANDY CLAY, VERY ML STIFF-HARD, SLIGHTLY DAMP	FILTER PACK OF LONESTAR 2/12 SAND PLACED THROUGH CENTER OF AUGER 18-35 FEET.
								SW DARK YELLOW BROWN MEDIUM SAND, LOOSE-DENSE, DAMP, SLIGHT HC ODOR	WELL CONSTRUCTED OF 2-INCH DIAMETER PVC SCHEDULE 40 CASING. SOLID CASING 0-20 FEET. 0.010 IN. SLOTTED CASING 20-35 FEET. SEDIMENT CAP AT BOTTOM.
15	X		28	ND	ND			COLOR LIGHTENS	WELL SURGED FOR 5 MINUTES DURING CONSTRUCTION TO SETTLE SAND.
20	X		39	ND	ND				
25	X		46	1645	ND			SM OLIVE GRAY SILTY MEDIUM SAND, DENSE, DAMP-MOIST, HC ODOR.	
								SATURATED BELOW 26 FEET	
30	X		46	ND	ND			ML LIGHT OLIVE GRAY MICACEOUS SILT, DENSE-VERY DENSE, WET	
35	X		44	ND	ND				
40								TOTAL DEPTH 35 FEET NO CAVING GROUNDWATER ENCOUNTERED DURING DRILLING AT ~26 FEET.	
45									



2902 LYTTON STREET  
 SAN DIEGO, CA 92110